

OERTZEN®

... for a cleaner world ☀

High-Pressure Cleaning Everywhere Commercial Series 30/31



High-pressure cleaners must be flexible, mobile and powerful to meet the customer's demands. Cost/performance ratio should be considered as well as consumption of water and electric power. With its commercial Series 30/31 OERTZEN offers a new program for cleanliness up to 250 bar. Most advanced technology as well as excellent quality is what the customer gets.

Robust and durable motors are available in single phase, three phase as well as gasoline and diesel units.



OERTZEN supplies cleanliness, quality and power for:

- Feeder farms
- Municipal services
- Drain cleaning services
- Commercial Light Industry
- Building maintenance
- Painting Industry
- Food Industry
- Swimming pools
- Hotels and restaurants
- Supermarkets



CE

High-Pressure Cleaning Everywhere Commercial Series 30/31

Cleaning, disinfecting, pipe cleaning – without problems

Cold water high-pressure cleaner Series 30/31 from OERTZEN come with axial piston pumps as well as plunger pumps which are directly flanged to the engine/motor.

Both systems give you low noise level and quiet running throughout hard, continuous and strenuous work.

All electrical units are standard with start/stop system. Closing spray

pistol cuts off the machine – opening spray pistol starts it again. Gasoline and diesel units are equipped with a thermo valve. Prior to pump overheating a thermo valve will release a small amount of hot water and simultaneously replace the hot water with cold water therefore not damaging the pump.

The electrical units of 30/31 Series have integrated hose reels and frame tanks for detergents.

Gasoline and Diesel units use an external chemical canister.

With high-pressure cleaners of 30/31 Series every job can be done quickly and efficiently. These machines comply with all national and European safety regulations.

CE stands for fulfillment of all relevant national and European (EN) safety regulations.

Technical data	305 CX	322 KL	318 Mobil HB	318 Mobil D
Flow rate max.	600 l/h	960 l/h	960 l/h	960 l/h
Unloading pressure	160 bar	210 bar	270 bar	230 bar
Working pressure max.	150 bar	190 bar	250 bar	210 bar
Pump speed	2800 1/min	1420 1/min	3400 1/min	3400 1/min
Pump system	axial	plunger	plunger	plunger
Voltage	230V/1~50 Hz	400V/3~50 Hz	-	-
Drive	electric	electric	gasoline	diesel
Connecting power	3.0 kW	5.1 kW	9.6 kW	7.5 kW
Thermo valve	-	-	+	+
Dimensions (LxWxH mm)	380x330x840	750x390x860	750x580x1100	820x720x650
Weight (net)	24 kg	61 kg	64 kg	115 kg
Order No.	10.000.103	10.000.140	10.000.416	10.000.415

Technical data are subject to alterations without notice.

Serial equipment: 12 m hp hose, spray lance with pistol, vario and turbo nozzle (322 KL: 15 m hp hose, vario/turbo nozzle, 318 Mobil D and HB: 10 m hp hose, double lance with pressure regulation), 5 m electric cable with plug (305 CX, 322 KL).



Agriculture: high-pressure cleaning machines and tools



Public baths and pools: no splashing water with floor cleaning device BRW



Facility service: high-pressure washroom cleaning - easy and effective

OERTZEN appointed dealer:

